

(12) UK Patent Application (19) GB (11) 2 272 766 (13) A

(43) Date of Printing by UK Office 25.05.1994

(21) Application No 9325998.4

(22) Date of Filing 29.06.1992

(30) Priority Data

(31) 912796

(32) 17.07.1991

(33) NO

(86) International Application Data

PCT/NO92/00116 En 29.06.1992

(87) International Publication Data

WO93/02345 En 04.02.1993

(71) Applicant(s)

Bjorn Dybdahl

Lillesund Terrasse 4D, N-5500 Haugesund, Norway

(72) Inventor(s)

Bjorn Dybdahl

(74) Agent and/or Address for Service

Stevens, Hewlett & Perkins

1 Serjeant's Inn, Fleet Street, LONDON, EC4Y 1LL,

United Kingdom

(51) INT CL⁵

G01N 1/10 1/20

(52) UK CL (Edition M)

G1B BCE

(56) Documents Cited by ISA

DE 003146928 A1

US 4294124 A

US 3803921 A


US 3747411 A

(58) Field of Search by ISA

INT CL⁵ G01N 1/10 1/20

(54) Isokinetic sampling apparatus

(57) The invention relates to an apparatus enabling isokinetic sampling of fluid flowing under high pressure in a tank (1), a separator, a heat exchanger or other container/pipe assigned at least one sampling point (2). In order to allow rational sampling, overcoming the problems due to said high pressure, the isokinetic sampling apparatus comprises a pressure fluid-operated cylinder (79) connected or connectable to, respectively, to a shut off valve (6, 6') which in its turn is connectable to said sampling point (2). When the shut off valve (6, 6') occupies the open position, it allows the passage of the piston rod (8) of the cylinder (7 - 9). The piston rod (8) is tubular and may consist of two concentric pipes (8', 8''). The free end of the inner pipe (8') is formed for easily releasable (exchangable) mounting of a probe (11) equipped with at least one orifice plate (14), in that the stroke of the piston (9) which preferably is variable, is such that the probe (11) with its orifice plate (14) may be pushed into said tank (1), etc., laterally of the fluid flow and take out fluid samples across at least most of the cross-sectional area of the fluid flow.



GB 2 272 766 A